

world class | shrink wrap

Automatic L-Sealer with Heat Shrink Tunnel MES 700 Series with 300 Series

For higher speed applications we offer a range of Automatic L-Sealers providing excellent performance and value for money. The complete system consists of a Fully-Automatic L-Sealing machine and Heat Shrink Tunnel with shrink wrapping speeds of up to 40 packs per minute. An automatic conveyor feeds the product into the film. The machine then measures the length of the product to allow the sealing jaws to operate automatically to produce the sealed bag. The film, which is trimmed off during the packaging process, is automatically wound up on the waste film take-up reel. It is then automatically conveyed into the high capacity Heat Shrink Tunnel for excellent shrink results all around the package.



Key benefits



- Optional combinations of standard **L-Seal Bar** and vertical motion available.



- **Film Dispenser** sliding carriageway under the machine to save space.



- Small footprint, **Heat Shrink Tunnel** optional closed pitch rollers for small products.

SHRINK



WRAP

technical data

	MES 700-80
Speed	15 - 40 Packs Per Minute / 900 – 2,400 Per Hour Maximum*
Sealing Dimension	40-250mm(l) x 30-300mm(w) x 5-80mm(h) (Product height dependant)
Film Type	Polyolefin Centre folded 8-80um
Maximum Film Reel Width	350mm
Safety	EN13849
Machine Dimensions	3000mm(l) x 1450mm(w) x 1390mm(h) (Includes Heat Tunnel)
Power Supply	250V 50Hz 13amp Single Phase
Max Power Consumption	1600W
Working Pressure	6 Bar
Machine Weight	460kg

* Maximum for this range, output speed depends on pack size. Other range, speeds and pack size capabilities are available

Options Available

Closing Conveyor, Product Collating, Polyethylene Blades, Bespoke Safety Levels, Alternative PLC's, Low Film Warning, Line Integration, Stainless Steel, Opposite Handing

	MES 313 Shrink Tunnel
Chamber Dimension	400mm(w) x 200mm(h) x 800mm(l)
Power Supply	400V 50Hz 3 Phase + Neutral (Other Voltages Available)
Max Power Consumption	7200W
Machine Weight	247kg

Options Available

Close Pitch Rollers, Opposite Handing, Stainless Steel

